



PIPE INVENTORY

SEAMLESS

½" - 24"	ASTM / ASME A/SA106-B / CSA Gr. 290 Cat I	STD / XS & True Schedules to 160 / XXS
	ASTM / ASME A/SA333-6 / CSA Gr. 290 / 359 Cat II & III M45C	STD / XS & True Schedules to 160 / XXS (<i>Note: 1 & 3</i>)
2" - 16"	CSA Gr. 448 Cat II M45C / API 5L / X65 PSL-2	STD - SCH. 80 (<i>See Note: 1</i>)
30" - 36"	ASTM / ASME A/SA106-B / A/SA333-6	STD / XS

WELDED

ERW

8" - 24"	CSA Gr. 290 Cat I / ASTM / ASME A/SA53-B / API 5L-B / X42 PSL-2	.250" WT, STD & XS
----------	---	--------------------

LSAW / DSAW

26" - 60"	CSA Gr.290 Cat II CVN M45C / DWTT M10C / API 5L-B / X42 PSL-2	Miscellaneous Schedules from STD to .750" WT (<i>See Note: 2</i>)
18" - 36"	CSA Gr. 359 Cat II M45C / API X52 PSL-2	STD & XS (<i>See Note: 1</i>)
20" - 48"	CSA Gr.359 Cat II CVN M45C / DWTT M10C / API X52 PSL-2	Miscellaneous Schedules from STD to 1.00" WT (<i>See Note: 2</i>)
18" - 48"	CSA Gr. 448 / 483 Cat II M45C / API X65 PSL-2	Miscellaneous Schedules from STD to 1.00" WT (<i>See Note: 1</i>)
20" - 48"	CSA Gr.448 Cat II CVN M45C / DWTT M10C / API X65 PSL-2	Miscellaneous Schedules from STD to 1.00" WT (<i>See Note: 2</i>)
20" - 48"	CSA Gr.483 Cat II CVN M45C / DWTT M10C / API X70 PSL-2	Miscellaneous Schedules from STD to .750" WT (<i>See Note: 2</i>)
30" - 48"	ASTM A671 CC70 Class 32	Supplementary S2 (M50C), S3, S4, S7, S14 Testing Fully compliant with NACE MR0103/ISO 17945 & Nace MR0175/ISO15156

Note 1: Cat II LSAW Charpy V Notch, Drop Weight Tear Test, and Fracture Appearance at M45C in full compliance with CSA Z245.1 SMLS, Charpy V Notch at M45C in full compliance with CSA Z245.1

Note 2: Cat II LSAW Charpy V Notch at M45C, Drop Weight Tear Test and Fracture Appearance at M10C in full compliance with CSA Z245.1

Note 3: Cat III SMLS 20" & 24", Charpy V Notch at M45C in full compliance with CSA Z245.1

MISCELLANEOUS ITEMS

- | | |
|---|-----------------|
| Pipe cutting | Stainless steel |
| Coating | Alloy |
| Larger custom sizes available, upon request | |